

UNITA' ASPIRANTI TRIFASE / THREE-PHASE SUCTION UNITS



MODELLO / MODEL	UTS 085	UTS 130	UTS 160	UTS 220	UTS 300	UTS 400	UTS 550	UTS 750	UTS 110
Alimentazione (V-Hz) Power supply (V-Hz)	400 – 50/60								
Potenza motore (kW) Motor power (kW)	0.85	1.3	1.6	2.2	3	4	5.5	7.5	11
Produzione oraria max (kg/h)* Max throughput (kg/h)*	220	320	360	460	520	630	1090	1530	2540
Depressione statica (mbar) Static depression (mbar)	160	190	210	240	270	440	440	440	440
Rumorosità massima (dBA) Noise max level (dBA)	< 80								
Peso approssimativo (kg) Approx. Weight (kg)	30	32	35	40	45	68	94	130	290

* Materiale con p.s.a.: 0,65 kg/dm³ - Distanza verticale: 4m - Distanza orizzontale: 5m / Material with bulk density.: 0,65 kg/dm³ - Vertical distance: 4m – Horizontal distance: 5m

CARICATORI TRIFASE / THREE-PHASE LOADERS

MODELLO / MODEL	CTS 2	CTS 4	CTS 6	CTS 10	CTS 14	CTS 20	CTS 30	CTS 50	CTS 80	CTS 110
Capacità (dm ³) Capacity (dm ³)	2	4	6	10	14	20	30	50	80	110
Peso (kg) Weight (kg)	6	8	12	13	15	18	19	22	26	40

UNITA' FILTRANTI / FILTERS UNIT

MODELLO / MODEL	UFS 50	UFS 100	UFS 200	UFS 300	UFS 400
Materiale filtro Filter material	Cellulosa Cellulose	Cellulosa Cellulose	Cellulosa Cellulose	Cellulosa Cellulose	Cellulosa Cellulose
Grado di filtrazione (μ) Filtering grade (μ)	2	2	2	2	2